

3/pts

10/534089

JCO6 Rec'd PCT/PTO 06 MAY 2005

-1-

Tubing Connection Kit and Method

This invention concerns the connection of tubing components to pipes, and has particular relevance to air-conditioning systems.

The global market for air-conditioning systems has risen dramatically in the last decade and looks set to continue to expand, for example into Eastern Europe. Currently, the most advanced air-conditioning system in common use is the VRV or Variable Refrigerant Volume system. This system comes in two types: Acooling only@ which is a two-pipe system, or a three pipe system which performs cooling and heating providing heating through recognised heat-pump technology.

A network of pipes is installed around the building to supply refrigerant to the relevant cooling coils (Aair handlers@) in the required areas. Figure 1 shows a known apparatus for assembly into such a network. A metal tubing component 1 is shown as a bifurcated Y-shaped junction to be connected to a metal pipe 2. The tube component 1 comprises several sections of different diameter, for example the first branch of the junction has two in-line sections X_1 and X_2 , while the second branch has three in-line sections: Y_1 , Y_2 and Y_3 to enable the component to be fitted to various standard, i.e. commercially accepted, sizes of pipe 2. When the component is to be fitted, the diameter of pipe 2 is determined and the correct diameter section of the component 1 is used to enable the pipe 2 to be accommodated within the section. In the figure shown, section X_2 has the correct diameter to allow pipe 2 to be inserted within it. If however pipe 2 was wider, then section X_1 would have to be used. In that case, the component would be cut off at section X_1 to allow insertion of the pipe 2. To fix the pipe 2 within the end section of component 1, the pipe and section are welded together. This is a cumbersome operation, especially since it is necessary to purge the weld region with nitrogen in order to prevent oxidation of the metal. Accordingly, the connection of tubing component 1 to pipe 2 is intricate and subsequently expensive and prone to error and fire risk, and takes an excessively long time to complete.

It is an object of the present invention to provide a connection kit and method which overcome the above problems. This is achieved by the use of cold jointing means with a correspondingly resized tubing component.

In accordance with a first aspect of the present invention there is provided a kit of parts comprising a tubing component having at least two in-line sections with different external diameters and a set of connection means, each connection means having dimensions such that it may be joined to the tubing component at a respective section.

Preferably, each connection means comprises a locking ring.

The kit of parts may be used in fabricating an air-conditioning system.

In accordance with a second aspect of the present invention there is provided a method of connecting a tubing component to a pipe comprising the steps of:

- providing a tubing component with at least two in-line sections with different external diameters;
- selecting a section with a substantially similar diameter to that of the pipe;
- if the selected section is not at an end of the tubing component, cutting the tubing component in the vicinity of the selected section so that the selected section is at an end of the tubing component;
- providing a set of connection means in a range of sizes;
- selecting a connection means of suitable dimensions for joining to the selected section; and
- joining the selected connection means to the tubing component at the selected section.

Preferably, each connection means comprises a locking ring.

The invention will now be described by way of example with reference to the following figures, in which:-

Figure 1 shows a conventional pipe assembly;

Figure 2 shows unconnected apparatus according to an embodiment of the present invention; and

Figure 3 shows the apparatus of the embodiment in a connected state.

Referring now to Figures 2 and 3, an assembly is shown according to an embodiment of the invention. Starting with Figure 2, again it is desired to connect a tubing component 1' to a pipe 2.

The tubing component 1' again comprises several sections of various external diameters, for example the in-line sections X₁', X₂', X₃' and X₄' of a first branch and in-line sections Y₁', Y₂' and Y₃' of a second branch. However, with this embodiment the diameters of the sections are set to be standard, i.e. commercially accepted and available, sizes. Since the pipe 2 is also of a standard diameter, it is possible to select a section which has the same diameter as the pipe 2. In the example shown in the figure, section X₂' has the same diameter as the pipe, and therefore the component is cut at section X₂' as shown. Clearly it is also possible to select a section of the second branch to enable this branch to be connected also.

Connection between the component 1' and pipe 2 is achieved by use of a connection means 3, which in the present embodiment comprises a locking ring. A suitable locking ring for this purpose is for example manufactured by Vulkan Lokring, Rohrverbindungen GmbH & Co. KG of Herne, Germany. Connection is achieved by inserting the ends of the pipe and component into the locking ring as shown, the ends being covered with a sealing preparation beforehand if necessary. A compression device is then used to squeeze the two end rings 4 of the locking ring together, which compresses the ends and holds them tightly and sealingly within the connection means. The compression device will preferably comprise a manually operable tool, which uses a ratchet arrangement to assist the user in forcing the rings together. A powered compression device is also available, and both of these devices are manufactured by Vulkan Lokring for example. The connected assembly is shown in Figure 3.

The advantage of using such a connection means is that the join can be done cold, i.e. without welding, thus reducing the complexity, time and cost of the assembly operation. Furthermore, no expensive or complex equipment is needed to fit the connection means.

A plurality of connection means of different sizes will be provided, allowing the tubing component to be fitted to a variety of sizes of pipe by appropriate selection of component width section and connection means.

Although the invention has been described with reference to the embodiments above, there are many other modifications and alternatives possible within the scope of the claims. For example, any suitable cold connection means may be used in place of the locking ring.

CLAIMS

1. A kit of parts comprising a tubing component having at least two in-line sections with different external diameters and a set of connection means, each connection means having dimensions such that it may be joined to the tubing component at a respective section.
2. A kit according to Claim 1, wherein each connection means comprises a locking ring.
3. A kit of parts according to Claim 1, for use in fabricating an air-conditioning system.
4. A method of connecting a tubing component to a pipe comprising the steps of:
 - providing a tubing component with at least two in-line sections with different external diameters;
 - selecting a section with a substantially similar diameter to that of the pipe;
 - if the selected section is not at an end of the tubing component, cutting the tubing component in the vicinity of the selected section so that the selected section is at an end of the tubing component;
 - providing a set of connection means in a range of sizes;
 - selecting a connection means of suitable dimensions for joining to the selected section; and
 - joining the selected connection means to the tubing component at the selected section.
5. A method according to Claim 4, wherein each connection means comprises a locking ring.

Abstract

A kit of parts comprises a tubing component 1' having at least two in-line sections with different external diameters and a set of connection means 3, each connection means having dimensions such that it may be joined to the tubing component at a respective section X.

Figure 2

CHICAGO/#1359770.1

INTERNATIONAL SEARCH REPORT

PCT/GB2004/004436

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 F16L25/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F16L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EP0-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 2 288 860 A (ADAMS ALAN JAMES) 1 November 1995 (1995-11-01) page 5, line 4 - page 6, line 14; figures 1,2	1,3,4
X	GB 2 326 453 A (BURCHFIELD ANTHONY JOHN) 23 December 1998 (1998-12-23) page 1, line 20 - page 1, line 44; figures 1-3	1,3,4
X	GB 721 656 A (THOMAS CECIL GREEN) 12 January 1955 (1955-01-12)	1,3,4
Y	page 1, line 50 - page 1, line 81; figures 1,2	2,5
	----- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the International filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the International filing date but later than the priority date claimed

- "T" later document published after the International filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the International search

28 January 2005

Date of mailing of the International search report

04/02/2005

Name and mailing address of the ISA

European Patent Office, P.B. 6818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Donnelly, C

INTERNATIONAL SEARCH REPORT

PCT/GB2004/004436

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 606 658 A (BBC BROWN BOVERI & CIE) 18 August 1948 (1948-08-18) page 1, line 72 - page 1, line 86; figure 6 -----	1, 3, 4
Y	DE 100 13 568 C (MAPRESS GMBH & CO KG) 7 June 2001 (2001-06-07) the whole document -----	2, 5

INTERNATIONAL SEARCH REPORT

Information on patent family members

PCT/GB2004/004436

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB 2288860	A	01-11-1995	NONE	
GB 2326453	A	23-12-1998	NONE	
GB 721656	A	12-01-1955	NONE	
GB 606658	A	18-08-1948	NONE	
DE 10013568	C	07-06-2001	DE 10013568 C1 WO 0169116 A1	07-06-2001 20-09-2001